

Hunter 350 Product Specifications

Engine

Type	Single Cylinder, 4 Stroke, Air-Oil Cooled
Displacement	349cc
Bore x Stroke	72 x 85.8 mm
Compression Ratio	9.5 : 1
Maximum Power	20.2 bhp @ 6100 rpm
Maximum Torque	19.9 lb-ft @ 4000 rpm
Ignition System	Electronic Fuel Injection (EFI)
Clutch	Wet, Multi-Plate
Gearbox	5 Speed, Constant Mesh
Lubrication	Wet Sump, Forced Lubrication
Engine Oil	SAE 15W-50 API, SL Grade, JASO MA2 Semi Synthetic
Fuel Supply	Electronic Fuel Injection
Air Cleaner	Paper Element
Engine Start	Electric

Chassis & Suspension

Type	Twin Downtube Spine Frame
Front Suspension	Telescopic, 41mm Forks, 130mm Travel
Rear Suspension	Twin Tube Emulsion Shock Absorbers w/ 6-Step Adjustable Preload, 90mm Travel

Dimensions

Wheelbase	53.94"
Ground Clearance	5.93"
Length	80.9"
Width	31.5" (without mirrors)
Height	41.54" (without mirrors)
Seat Height	31.1"
Curb Weight	399 lbs (with 90% fuel & oil)
Fuel Capacity	3.43 gal

Brakes & Tires

Front Tire	110/70 - 17" - 54P
Rear Tire	140/70 - 17" - 66P
Front Brake	300 mm Disc, Bybre Twin Piston Floating Caliper
Rear Brake	270 mm Disc, Bybre Single Piston Floating Caliper
ABS	Dual Channel

Electricals

Electrical System	12V - DC
Battery	12V, 8 AH, VRLA (Maintenance free)
Head Lamp	12V, H4-60/55W (Halogen) w/ LED Light Guide
Tail Lamp	12V, LED 4.8/0.5
Turn Signal Lamp	12V, LED